



# Conference USB Microphone Solvision -N2

 The Solvision N2 is An engineering-grade Wired Microphone with Omnidirectional Pattern USB Connector for Podcasting, Video Conference Gaming, YouTube Streaming, Recording etc.





#### **Features**

- Designed for video conferencing and other applications such as lecture capture and distance learning
- USB Microphone
- USB C interface for audio
- Power Source Corded Electric
- Universal PC compatibility through standard UAC 2.0 & Type C (USB Audio Class) driver
- Works with popular soft codec and UC clients such as Microsoft®
  Teams, Zoom™, Blue Jeans™, Slack™, WebEx®, and GoToMeeting®
- Omnidirectional polar pattern picks up sounds from all directions at very high sensitivity with a focus on clarity and reliability.
- Pickup pattern to capture the subtle sound from 360°.
- Pick up distance is also long enough to not miss out on any important transmissions without any distortions, In the pickup range(5m/16.4ft)
- Hd voice / wideband audio.
- One Button Mute: The built-in indicator light informs the status (blue: working, No blue: mute). It makes your meeting more efficient while you multitask during a call to mute your mic with only one soft touch.



Compatible with Various Video Conferencing System and Web Conferencing Software with DSP chip AGC and Auto Sensitivity Adjustment.



## **Specifications**

- Noise cancellation interference from the background noise while interacting.
- 1.5m shielded & braided USB cable with gold plated contact is also tangle-free.
- Built-in filter sponge eliminates unwanted noise ensuring only ultra-clear audio which to is transmitted goes into the mic, filtering out any extra noise.
- Wide frequency response and high output for clear & vibrant vocal performance.
- Multi-system compatibility Compatible with windows series, Mac, Linux and other systems No need to install drivers plug and play.
- Microphone can be mounted on a wall, or inverted for ceiling installation.
- Polar pattern: Omnidirectional
- Type :condenser microphone
- Signal to noise ratio: 95dB
- Frequency response speed: 20Hz-20KHz
- Max spl : 110dB
- Susceptibility: -40dB ± 2dB (0dB = 1 1v/pa, at 1)
- Product name: condenser microphone
- Recommended :indoor
- Pickup range :3 meters
- Maximum sampling rate :96 125kHz/16Bit
- Safety CE, c-UL, UL

### **SOLVISION TECHNOLOGY**

27 Elder Road, Working Surrey GU24 9HB UK info@solvisionav.com 9 A, Blackwood Avenue, Mentone, VIC- 3194 salesaustralia@solvisionav.com 629 Redstone Drive NE, Calgary AB, T3N, 1KB Alberta salescanada@solvisionav.com

#### **SOLVISION INDIA**

D-9th Floor SAS Tower-B Sector -38 Gurugram Haryana- 122001 salesindia@solvisionav.com